

THRONE OIL 5W-40

Description:

It is a fully synthetic engine oil that meets the latest technical standards developed for high performance engines produced with the combination of high performance additives in state-of-the-art synthetic base oils.

Usage Areas:

It is used in all high-performance modern vehicles, passenger cars and light commercial vehicles.

Benefits and Advantages Provided:

- It provides the best performance characteristics against abrasion, wear and sediment formation.
- It protects the engine against wear by providing fast oiling of the engine parts during the first operation thanks to excellent flow in cold weather conditions.
- Oxidation resistance is excellent. It provides high fuel savings and a longer oil change interval.
- By means of its high viscosity index, it has superior performance in hot and cold weather.

Performance: It compensates the performance specifications API SM/CF; ACEA A3/B4-04; MB 229.3; VW 502.00/505.00; JASO SG+; RN 0700, 0710.

Typical Properties:

Physical Property	Method	5W-40
Density, g/cm ³ , 15°C	ASTM D 4052	0,857
Kin. Viscosity, cSt, 40°C	ASTM D 445	92,6
Kin. Viscosity, cSt, 100°C	ASTM D 445	14,5
Viscosity Index	ASTM D 2270	163
Pour Point, °C	ASTM D 97	-36
Flash Point, °C	ASTM D 92	230

** The values given in the table are typical and they may vary from production to production.*